



For exact location download the Highways Toolbox from Google Play store.

What3words/// submit.labels.occur



THIS DRAWING MAY BE USED ONLY FOR THE PURPOSE INTENDED AND ONLY WRITTEN DIMENSIONS SHALL BE USED

NOTES

1. Sign locations are indicative only and exact locations need to be determined on site
2. All traffic signs shall comply with Chapter 8 of the Traffic Signs Manual
3. Maximum distance between any two temporary traffic signs to be 200m. Minimum distance between any two temporary traffic signs to be 20m.
4. Temporary traffic signs shall not occur within 100m of an existing level crossing. Before crossing or signpost junction without the consent of the Engineer. The Engineer shall consult with the authority responsible for any of these types of facility prior to traffic management being installed in adjacent areas.
5. Coning shall be installed at 45° to the edge of carriageway, as generally indicated.
6. Cable crossing protectors and PT10SP/2013 signs shall be provided whenever control cables cross a section of carriageway open to traffic.
7. The signal control mechanism shall normally be placed in a location from which it is possible to view all approaches to the site.
8. Duplicate primary signal to be installed as instructed.
9. Lane width just the works to be 3.7m maximum, 3.25m desirable minimum, 3.0m absolute minimum.

KEY



DRAFT

Revision Details	By	Date	Suffix
	Chk		

Drawing Number **28091.004**

Project Title **A40 Cuckoo Lane Witney**

Drawing Title **Speed restriction**

Scale at A1:
NTS

Drawn & Checked: J.REYNOLDS
Date: 10/06/22

Approved By: M.FENNER

Suitability: **FOR CONSTRUCTION**



This map is based upon Ordnance Survey material with the permission of Ordnance Survey on behalf of the Controller of Her Majesty's Stationery Office. © Crown copyright. Unauthorised reproduction infringes Crown copyright and may lead to prosecution or civil proceedings. (100036446) (2022)